

FIRST IN **QUALITY** **BUILT TO** **LAST**

CASE TAPERS

BB-2
BB-2/SS
TB-2
SB-2EX
SB-2EX RANDOM
SB/TB-2
EASY PACKER
SB-2F/C

PRODUCT HANDLING

EX-CF
CONVEYORS
ACCUMULATION TABLES
VCTS



EASTEY
First in Quality. Built to Last.

1 (800) 835-9344 www.eastey.com

BB-2
BOTTOM BELT CASE TAPER

COST-EFFECTIVE CASE SEALING

BB-2 features self-centering side rails, a rugged bottom belt drive, and heavy-duty mast that easily adjusts to handle a variety of case sizes at a cost-effective price.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	5.0"	5.0"	4"
Maximum Box Size	Infinite	21.0"	20.5"
TAPING SPECIFICATIONS			
Belt Speed	60 fpm		
Tape Speed	30 cases per min.		
Air Requirements	None		



SB-2EX
SIDE BELT CASE TAPER

WIDE STANDARD CASE RANGE

The SB-2EX's side belts are great for light or heavy weight, narrow or small boxes. It is ideal for void-fill cases where the packaged product does not support the box.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	5.0"	4.0"	4.0"
Maximum Box Size	Infinite	19.5"	19.5"
TAPING SPECIFICATIONS			
Belt Speed	75 fpm		
Tape Speed	30 cases per min.		
Air Requirements	None		



EASY PACKER
CASE TAPING SYSTEM

COMPACT CASE ERECTING, PACKING AND SEALING

Designed to streamline manual case packing, the Easy Packer is supplied with an 48" anvil packing station extended side rails, and flap closing bars to assist with the packing and sealing process.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	5.0"	4.0"	4.0"
Maximum Box Size	Infinite	19.5"	19.5"
TAPING SPECIFICATIONS			
Belt Speed	75 fpm		
Tape Speed	20 cases per min.		
Air Requirements	None		



BB-2/SS
BOTTOM BELT CASE TAPER

IDEAL FOR WASHDOWN CONDITIONS

Stainless steel construction coupled with a single drive washdown motor and aggressive drive belts make BB-2/SS ideal for wash down conditions.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	5.0"	5.0"	4"
Maximum Box Size	Infinite	21.0"	20.5"
TAPING SPECIFICATIONS			
Belt Speed	60 fpm		
Tape Speed	30 cases per min.		
Air Requirements	None		



SB-2EX RANDOM
RANDOM SIDE BELT CASE TAPER

RANDOM CASE SIZE SEALING

SB-2EX Random allows users to run a variety of case sizes without having to manually adjust for each box. The system automatically adjusts the side rails and tape head height for different size cases.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	5.0"	4.5"	4.5"
Maximum Box Size	Infinite	23.0"	23.0"
TAPING SPECIFICATIONS			
Belt Speed	75 fpm		
Tape Speed	15-20 cases per min.		
Air Requirements	80 PSI		



SB-2/FC
AUTOMATIC UNIFORM CASE TAPER

AUTOMATED CASE CLOSING AND SEALING

The SB-2/FC side belt case taper is designed to automatically close all four case flaps and seal the top and bottom. The adjustable plow system provides the utmost flexibility for varying types of carton sealing applications.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	5.0"	4.5"	4.5"
Maximum Box Size	24.0"	19.5"	19.5"
TAPING SPECIFICATIONS			
Belt Speed	75 fpm		
Tape Speed	20 cases per min.		
Air Requirements	85 PSI		



TB-2
BOTTOM BELT CASE TAPER

FOR TALL AND NARROW CASES

TB-2 utilizes top and bottom drives and a dual mast for greater tape head stability. It is ideal for tall and narrow or over-filled cases.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	5.0"	6.0"	4.5"
Maximum Box Size	Infinite	19.5"	19.5"
TAPING SPECIFICATIONS			
Belt Speed	75 fpm		
Tape Speed	30 cases per min.		
Air Requirements	None		



SB/TB-2
SIDE BELT & TOP BELT CASE TAPER

DESIGNED FOR EXTRA LARGE CASES

The SB/TB's top and side belts are great for over-sized, heavy weight cases that are too large for most case sealing equipment.

BOX SPECIFICATIONS			
	Length	Width	Depth
Minimum Box Size	4.5"	6.0"	4.0"
Maximum Box Size	Infinite	27.5"	27.5"
TAPING SPECIFICATIONS			
Belt Speed	75 fpm		
Tape Speed	30 cases per min.		
Air Requirements	None		



TAPEHEADS
EASTEY TAPEHEADS

TAPEHEAD OPTIONS

Two tape head options are available for Easteys line of case tapers: the EZ and EX Models. These heavy-duty tape applying cartridges incorporate bronze bushings and other top of the line materials to provide trouble-free service. These tapeheads drop into the bottom of the machine and can be removed in an upward motion from the top taping assemblies. Both versions of top and bottom tapeheads can be removed instantly without tools.

In addition, Easteys offers a full line of specialty application tapeheads and heads for competitive systems:

- Front L-Clip Tapehead
- EZ tapehead for 3M machines
- EZ tapehead for Dekka machines
- EZ tapehead for Loveshaw machines
- 2" or 3" tapeheads standard
- Custom widths available



PRODUCT HANDLING

EX-CF CARTON FORMER

COMPACT CASE FORMING AND PACKING
Designed for semi-automatic case forming and packing, the EX-CF will improve productivity and increase your ROI.

EX-CF SPECIFICATIONS	
Machinery Makeup	12 gauge powder coated steel
Conveyor Height Adj.	27" to 34.6"
Air Requirements	80 PSI
Electrical Requirements	None
BOX SPECIFICATIONS	
Minimum Box Size	7.5" (L) x 5.5" (W) x 3" (Depth)
Maximum Box Size	25" (L) x 20" (W) x 19.5" (Depth)



EASTEY CONVEYORS VARIABLE SPEED CONVEYORS

CONVENIENT PRODUCT TRANSPORT
Small footprint, seamless self-tracking belt, pre-drilled holes for printer hardware, and magnetic mounted control box make the Eastey Conveyor Series an ideal solution for case coding and product transport.

CONVEYOR SPECIFICATIONS	
Machinery Makeup	12 gauge powder coated steel
Variable Speed	Up to 100 fpm
Conveyor Height Adj.	20"-33.5" w/out casters 24" - 37.5" with
Electrical Requirements	110V 5A Single Phase
MODEL SPECIFICATIONS	
EC1248	48.9" (L) x 20.2" (W) x 12" (Conveyor W)
EC1848	48.9" (L) x 26.2" (W) x 18" (Conveyor W)
EC2472	72" (L) x 32.2" (W) x 24" (Conveyor W)



ACCUMULATION TABLES ROTARY ACCUMULATION TABLES

MANAGE PRODUCTION RATES
Eastey's Accumulating Tables are placed at the end of a production line to receive bottles, jars, cans, and containers after filling or cleaning. The accumulating table helps prevent costly backups and slowdowns in production.

TABLE SPECIFICATIONS	
Machinery Makeup	Industrial strength tubular steel frame
Working Height	Adjustable 27" to 37" height
Variable Speed	Up to 13 revolutions per minute
Electrical Requirements	115V or 220V, 5A single phase w/ ground
MODEL SPECIFICATIONS	
TT36	36" table diam. 24" base (L) 24" base (W)
TT48	48" table diam. 24" base (L) 24" base (W)



VCTS VERTICAL CASE TRANSPORT SYSTEM

CUSTOM CASE PRINTING MADE EASY
The VCTS is designed for off-line custom case printing and eliminates the need for pre-printed cases or expensive labeling equipment.

BOX SPECIFICATIONS	
	Width
Minimum Box Size	10.0" (Standard & XL)
Maximum Box Size	33.0" (Standard) 48" (XL)
MACHINE SPECIFICATIONS	
Belt Speed	72 fpm (approx. 50 - 10'x10' cases/min)
Input Hopper	Up to 90 flat single wall cases
Electrical Requirements	110 VAC, 60Hz, 4.0A
Air Requirements	80 PSI, 1/4 NPT Fitting





7041 Boone Avenue North, Brooklyn Park, MN 55428
(763) 428-4846 1 (800) 835-9344
www.eastey.com info@eastey.com



ENGAGE *technologies corporation*